

*制御電源 ±12V仕様

形名 (Type)	HC-L800V4B12	HC-LE10V4B12	HC-LE12V4B12	HC-LE15V4B12	HC-LE18V4B12	HC-LE20V4B12	HC-LE25V4B12	HC-LE30V4B12
定格電流 [If] (Rated current)	±800A	±1000A	±1200A	±1500A	±1800A	±2000A	±2500A	±3000A
飽和電流 [Is] (Saturation current)	±1200A	±2250A	±2700A	±3375A	±4000A	±4000A	±4000A	±5000A
直線性範囲 (Linearity limits)	0~±1000A	0~±2000A	0~±2500A	0~±3125A	0~±3500A	0~±3500A	0~±3500A	0~±4000A
定格出力 [Vh] (Rated output)	±4V±1%							
残留出力 [V0] (Residual output)	Within ±30mV							
直線性 (Output linearity)	Within ±1%							
応答速度 (Response time)	Within 10 μs(at di/dt=100A/μs)							
過渡特性 (Response performance)	Within 10%							
ヒステリシス巾 (Hysteresis Voltage range)	Within 30mV							
出力温度特性 (Output Temp. Coef.)	Within ±0.05%/°C							
残留出力温度特性 (Residual output Temp. Coef.)	Within ±2mV/°C							
制御電源 (Control power supply)	±12V±5%							
消費電流 (Consumption current)	Within 50mA							
使用温度範囲 (Operating Temp.)	-10°C~+80°C							
保存温度範囲 (Storage Temp.)	-15°C~+85°C							
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute							
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC							