

HC-MJ series

*制御電源 ±12V仕様

形名 (Type)	HC-MJE10V4B12	HC-MJE15V4B12	HC-MJE20V4B12	HC-MJE25V4B12	HC-MJE30V4B12	HC-MJE35V4B12	HC-MJE40V4B12
定格電流 [If] (Rated current)	±1000A	±1500A	±2000A	±2500A	±3000A	±3500A	±4000A
飽和電流 [Is] (Saturation current)	±2250A	±2400A	±2400A	±4800A	±4800A	±4800A	±4800A
直線性範囲 (Linearity limits)	0~±2000A	0~±2000A	0~±2000A	0~±4000A	0~±4000A	0~±4000A	0~±4000A
定格出力 [Vh] (Rated output)	±4V±1.5%						
残留出力 [V0] (Residual output)	Within ±30mV						
直線性 (Output linearity)	Within ±1%						
応答速度 (Response time)	Within 10 μs(at di/dt=100A/μs)						
過渡特性 (Response performance)	Within 10%						
ヒステリシス巾 (Hysteresis Voltage range)	Within 30mV						
出力温度特性 (Output Temp. Coef.)	Within ±0.1%/°C						
残留出力温度特性 (Residual output Temp. Coef.)	Within ±1.5mV/°C						
制御電源 (Control power supply)	±12V±5%						
消費電流 (Consumption current)	Within 50mA						
使用温度範囲 (Operating Temp.)	-40°C~+80°C						
保存温度範囲 (Storage Temp.)	-40°C~+85°C						
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute						
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC						