

*制御電源 ±15V仕様

形名 (Type)	HC-PVT010V4B15	HC-PVT20V4B15	HC-PVT30V4B15	HC-PVT40V4B15	HC-PVT50V4B15
定格電流 [If] (Rated current)	±10A	±20A	±30A	±40A	±50A
連続通電DC電流 (Continuously flowing DC current)	±13.8A	±13.8A	±23.3A	±23.3A	±35.4A
飽和電流 [Is] (Saturation current)	±27.6A	±46A	±69A	±69A	±138A
直線性範囲 (Linearity limits)	0~±20A	0~±33.3A	0~±50A	0~±50A	0~±100A
1次巻線線径 (Size of primary winding)	φ1.0	φ1.0	φ1.3	φ1.3	φ1.6
ターン数 (Turns)	5	3	2	2	1
定格出力 [Vh] (Rated output)	±4V±2% (RL=10kΩ) (excluding the residual output)				
残留出力 [V0] (Residual output)	Within ±100mV				
直線性 (Output linearity)	Within ±1%				
応答速度 (Response time)	Within 10μs (at di/dt=If/μs)				
過渡特性 (Response performance)	Within 10%				
ヒステリシス巾 (Hysteresis Voltage range)	Within 100mV				
出力温度特性 (Output Temp. Coef.)	Within ±0.1%/°C				
残留出力温度特性 (Residual output Temp. Coef.)	Within ±3mV/°C				
制御電源 (Control power supply)	±15V±5%				
消費電流 (Consumption current)	Within 60mA				
使用温度範囲 (Operating Temp.)	-10°C~+80°C				
保存温度範囲 (Storage Temp.)	-15°C~+85°C				
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute				
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC				