

HC-SL series

*制御電源 ±12V仕様

形名 (Type)	HC-SL050V4B12	HC-SL100V4B12	HC-SL150V4B12	HC-SL200V4B12	HC-SL250V4B12	HC-SL300V4B12	HC-SL350V4B12	HC-SL400V4B12
定格電流 [If] (Rated current)	±50A	±100A	±150A	±200A	±250A	±300A	±350A	±400A
飽和電流 [Is] (Saturation current)	±112.5A	±225A	±337.5A	±450A	±562.5A	±675A	±787.5A	±900A
直線性範囲 (Linearity limits)	0~±112.5A	0~±225A	0~±337.5A	0~±450A	0~±562.5A	0~±675A	0~±787.5A	0~±900A
定格出力 [Vh] (Rated output)	±4V±1.5% (RL=10kΩ)	±4V±1% (RL=10kΩ)						
残留出力 [V0] (Residual output)	Within ±50mV	Within ±30mV						
直線性 (Output linearity)	Within ±1%							
応答速度 (Response time)	Within 10 μs (The smaller one on either at di/dt=100A/μs or If/μs.)							
過渡特性 (Response performance)	Within 10%							
ヒステリシス巾 (Hysteresis Voltage range)	Within 30mV							
出力温度特性 (Output Temp. Coef.)	Within ±0.1%/°C							
残留出力温度特性 (Residual output Temp. Coef.)	Within ±3mV/°C	Within ±1.5mV/°C				Within ±1mV/°C		
制御電源 (Control power supply)	±12V±5%							
消費電流 (Consumption current)	Within 30mA							
使用温度範囲 (Operating Temp.)	-10°C~+80°C							
保存温度範囲 (Storage Temp.)	-15°C~+85°C							
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute							
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC							

HC-SL series

*制御電源 ±12V仕様

形名 (Type)	HC-SL450V4B12	HC-SL500V4B12	HC-SL550V4B12	HC-SL600V4B12	HC-SL650V4B12	HC-SL700V4B12	HC-SL750V4B12	HC-SL800V4B12
定格電流 [If] (Rated current)	±450A	±500A	±550A	±600A	±650A	±700A	±750A	±800A
飽和電流 [Is] (Saturation current)	±1000A	±1000A	±1000A	±1000A	±1000A	±1000A	±1000A	±1000A
直線性範囲 (Linearity limits)	0~±900A	0~±900A	0~±900A	0~±900A	0~±900A	0~±900A	0~±900A	0~±900A
定格出力 [Vh] (Rated output)	±4V±1% (RL=10kΩ)							
残留出力 [V0] (Residual output)	Within ±30mV							
直線性 (Output linearity)	Within ±1%							
応答速度 (Response time)	Within 10 μs (The smaller one on either at di/dt=100A/μs or If/μs.)							
過渡特性 (Response performance)	Within 10%							
ヒステリシス巾 (Hysteresis Voltage range)	Within 30mV							
出力温度特性 (Output Temp. Coef.)	Within ±0.1%/°C							
残留出力温度特性 (Residual output Temp. Coef.)	Within ±1mV/°C							
制御電源 (Control power supply)	±12V±5%							
消費電流 (Consumption current)	Within 30mA							
使用温度範囲 (Operating Temp.)	-10°C~+80°C							
保存温度範囲 (Storage Temp.)	-15°C~+85°C							
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute							
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC							