

*制御電源 土15V仕様

<電圧出力タイプ>

形 名 (Type)	HS-PKD050V4B15	HS-PKD100V4B15S	HS-PKD150V4B15S
定格電流 [If] (Rated current)	±50A	±100A	±150A
連続通電DC電流 (Continuously flowing DC current)	±50A	±72A	±108A
飽和電流 [Is] (Saturation current)	±125A	±250A	±375A
直線性範囲 (Linearity limits)	0~±100A	0~±200A	0~±300A
定格出力 [Vh] (Rated output)	+If	V0+4V±1% (RL=10kΩ)	
	-If	V0-4V±1% (RL=10kΩ)	
残留出力 [V0] (Residual output)		Within ±20mV	
直線性 (Output linearity)		Within ±0.5%	
二次巻線抵抗 (Second coil resistance)	Approx. 47Ω		Approx. 63Ω
応答速度 (Response time)	Within 1 μs (The smaller one on either at di/dt = 100A/μs or If/μs.)		
過渡特性 (Response performance)	Within 10%		
ヒステリシス巾 (Hysteresis Voltage range)	Within 20mV		
出力温度特性 (Output Temp. Coef.)	Within ±0.01%/°C		
残留出力温度特性 (Residual output Temp. Coef.)	Within ±0.8mV/°C		
制御電源 (Control power supply)	±15V±5%		
消費電流 (Consumption current)	20mA+(Input current/2500)		20mA+(Input current/3200)
使用温度範囲 (Operating Temp.)	-10°C~+80°C		
保存温度範囲 (Storage Temp.)	-15°C~+85°C		
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute		
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC		

*制御電源 土15V仕様

<電流出力タイプ>

形 名 (Type)	HS-PKD050A0025B15	HS-PKD100A005B15	HS-PKD150A005B15
定格電流 [If] (Rated current)	±50A	±100A	±150A
連続通電DC電流 (Continuously flowing DC current)	±50A	±72A	±72A
飽和電流 [Is] (Saturation current)	±100A	±150A	±150A
直線性範囲 (Linearity limits)	0~±100A (RL=100Ω~180Ω)	0~±150A (RL=120Ω)	0~±200A (RL=120Ω)
定格出力 [Ih] (Rated output)	+If	I0+25mA±1%	I0+50mA±1%
	-If	I0-25mA±1%	I0-50mA±1%
残留出力 [I0] (Residual output)		Within ±0.2mA	
直線性 (Output linearity)		Within ±0.5%	
二次巻線抵抗 (Second coil resistance)	Approx. 38Ω		Approx. 58Ω
応答速度 (Response time)	Within 1μs (The smaller one on either at di/dt = 100A/μs or If/μs.)		
過渡特性 (Response performance)	Within 10%		
ヒステリシス巾 (Hysteresis Voltage range)	Within 0.2mA		
出力温度特性 (Output Temp. Coef.)	Within ±0.01%/°C		
残留出力温度特性 (Residual output Temp. Coef.)	Within ±0.01mA/°C		
制御電源 (Control power supply)	±15V±5%		
消費電流 (Consumption current)	20mA+(Input current/2000)		20mA+(Input current/3000)
使用温度範囲 (Operating Temp.)	-10°C~+80°C		
保存温度範囲 (Storage Temp.)	-15°C~+85°C		
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute		
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC		