

## HC-PL series

\*Control power supply specification:  $\pm 15V$

Type	HC-PL05V4B15	HC-PL10V4B15	HC-PL15V4B15	HC-PL20V4B15	HC-PL25V4B15	HC-PL30V4B15
Rated current [If]	$\pm 5A$	$\pm 10A$	$\pm 15A$	$\pm 20A$	$\pm 25A$	$\pm 30A$
Continuously flowing DC current	$\pm 8.8A$	$\pm 8.8A$	$\pm 13.8A$	$\pm 13.8A$	$\pm 23.3A$	$\pm 23.3A$
Saturation current [Is]	$\pm 12.5A$	$\pm 25A$	$\pm 37.5A$	$\pm 37.5A$	$\pm 75A$	$\pm 75A$
Linearity limits	$0 \sim \pm 10A$	$0 \sim \pm 20A$	$0 \sim \pm 30A$	$0 \sim \pm 30A$	$0 \sim \pm 60A$	$0 \sim \pm 60A$
Size of primary winding	$\phi 0.8$	$\phi 0.8$	$\phi 1.0$	$\phi 1.0$	$\phi 1.3$	$\phi 1.3$
Turns	6	3	2	2	1	1
Rated output [Vh]	$\pm 4V \pm 2\%$ (RL=10k $\Omega$ )					
Residual output [V0]	Within $\pm 100mV$					
Output linearity	Within $\pm 1\%$					
Response time	Within 10 $\mu s$ (at di/dt=If/ $\mu s$ )					
Response performance	Within 10%					
Hysteresis Voltage range	Within 100mV					
Output Temp. Coef.	Within $\pm 0.1\%/^{\circ}C$					
Residual output Temp. Coef.	Within $\pm 2mV/^{\circ}C$					
Control power supply	$\pm 15V \pm 5\%$					
Consumption current	Within 30mA					
Operating Temp.	$-10^{\circ}C \sim +80^{\circ}C$					
Strage Temp.	$-15^{\circ}C \sim +85^{\circ}C$					
Dielectric withstand voltage	2500V AC 50/60Hz 1minute					
Insulation resistance	Not less than 500M $\Omega$ 500V DC					