

*Control power supply specification: $\pm 15V$

Type	HC-W050V4B15	HC-W100V4B15	HC-W150V4B15	HC-W200V4B15	HC-W250V4B15	HC-W300V4B15
Rated current [If]	±50A	±100A	±150A	±200A	±250A	±300A
Saturation current [Is]	±150A	±300A	±450A	±600A	±600A	±700A
Linearity limits	0～±150A	0～±300A	0～±450A	0～±500A	0～±500A	0～±600A
Rated output [Vh]	±4V±1.5%	±4V±1%				
Residual output [V0]	Within ±50mV	Within ±30mV				
Output linearity	Within ±1%					
Response time	Within 10 μ s (The smaller one on either at di/dt=100A/ μ s or If/ μ s.)					
Response performance	Within 10%					
Hysteresis Voltage range	Within 30mV					
Output Temp. Coef.	Within ±0.08%/°C					
Residual output Temp. Coef.	Within ±2.5mV/°C	Within ±1.5mV/°C				
Control power supply	±15V±5%					
Consumption current	Within 60mA					
Operating Temp.	-10°C～+80°C					
Strage Temp.	-15°C～+85°C					
Dielectric withstand voltage	2500V AC 50/60Hz 1minute					
Insulation resistance	Not less than 500MΩ 500V DC					